



hp TIJ2.5 Inkjet coder



Compact, robust and low-cost design but still performs high print efficiency.



■ Diverse Installation

- A compact unit TIJ printer with an angle-adjustable printhead and external photocell.
- Suitable for diverse installation demands.
- Be integrated with labeling machine and capping machine.




Print Efficiency

A cost-saving DJ1 brings you excellent print efficiency.

DJ1 has less components but keeps excellent inkjet printing technology to achieve users' production efficiency.

- Max 20 units of print per second.(Depend on print message length)
- High print speed:
 Aqueous ink: max 60 m

Aqueous ink: max 60 meters/min Solvent ink: max 75 meters/min



Print Message Content

Text, image, date, time, lot/batch number, shift code and static barcode objects. Other languages input by text builder.



Message lines from 1 line to 4 lines.

Print height: Max 4 options based on the number of message line.



Max. print length: When print height is 12.7mm, the max print length is 127 characters plus appendant 3 sets of printingmessages, total 508 characters.



Manage Print Jobs With Less Cost

- Create printing messages by easy-to-learn PC software or by Android smartphone.
- Max storage is 30 print jobs per file, only required printing messages can stay in DJ1 printer.
- Give a short description each print job to help users find the correct print job easily.
- 4 Transfer the data to DJ1 by a USB driver.





Less Function but Protect Correctness


A routine to help users avoid mistakes: To download required printing messages from a USB stick instead of giving the function to edit content by onsite DJ1. All an operator needs to do is to press the controller buttons to select print job and start printing.

Easy to Learn Software


- User-friendly interface design for PC software and Android App.
- Easy to build print messages with a clear preview section.
- Ink consumption calculation per print message.
- Append message function gives a capability to combine messages into 1 print job.
- Transfer the data to the printer by a USB stick.



Text builder function in logo list allows multiple languages input with various fonts.



Simply click and drag required message object into template grid, then start editing content.






Template grid

Touch drag and drop required message object into template grid, then start editing content.

Preview

Controller Operation

- ✓ 2.8" TFT LCD display.
- 6 simple buttons to operate.
- Multiple languages for the operation interface.
- ✓ Low ink LED indicator to build on the controller membrane.
- Few steps to adjust parameters and start printing.










Select Message


The short description of each message is given by user when user creates message by PC or Android App.

Coding and marking work can be simple when you work with DJ1.









Ink Cartridge

HP TIJ 2.5 technology A clean cartridge system ensures the best cartridge lifetime and keeps uptime.




- Hot-swapping cartridge Effortless to replace ink cartridge without downtime.
- Printing resolution 300 dpi x 300 dpi
- · Print speed can be up to 60 m/ min (aqueous-based ink) and 75 m/ min (solvent-based ink)
- Ink types aqueous ink, solvent ink and UV-curable ink for different substrates.

Smart Card



- A smart card on cartridge stores the cartridge print parameters information.
- Automatic ink identification allows parameters setting for each ink cartridge to achieve the best performance.



SPECIFICATIONS

Model DJ1

Technology hp TIJ2.5

Housing Aluminum casting

Display 2.8" TFT LCD display.

Power requirement AC 110-220v

Operation temperature 5°C to 45°C (41°F to 113°F)

Message Storage 30 print jobs

Print line 1~4 lines

Print height Max 4 options to select from depends on

the number of print line: 12.7mm, 6mm, 3mm, 1.5mm.

Print speed Max: 60m/min- Aqueous ink cartridge.

Max: 75m/min- Solvent ink cartridge.

Max print length 508 characters

Print resolution 300 dpi x 300 dpi

Max Ink throw distance 6mm is recommended.

LED indicators Power, Trigger, Alarm (ink low)

Any of languages text, lot and box number, Software function

date- time code, shift code, logo

Print font Two available fonts for printing: standard, bold

Multiple languages available.

Printer operation language

(Some languages' translation support may be required.)

Multiple languages available. PC software language

(Some languages' translation support may be required.)

Android app language English

Dimension (L/W/H) 202 x 143 x 120 mm

Weight 652g (excluding cartridge)

Optional Encoder, Bulk ink supply (aqueous ink)







АРЕПЛИВИ